

ELEVATOR TRAINING SET FM-AP30 (Basic Model)



3-floor elevator training set is designed as a sample for electromechanical control and PLC applications. Its transparent structure is preferred to examine the electrical connections and mechanical parts. 45x45 anodized aluminum sigma profile is used in the construction of the set.

All inputs and outputs necessary to run the elevator are taken out of the surface of the panel via 4 mm banana sockets. Also the states of the process can be easily followed by the LEDs which are connected to inputs and outputs of the elevator.

There are sliding door, cabin light which is activated by the electro-magnetic door lock, call and emergency stop buttons and 7-segment floor display in the elevator cabin.

Floor level and limit sensors, cabin balance weight mechanism, call buttons in the floors, 7-segment floor display, LEDs showing up/down movement and DC motor form the rest of the set.

- Supply voltage 220 VAC/ 50 Hz
- Short-circuit protected, Switch Mode 24 VDC/4.5 A Power Supply
- 4mm sockets for elevator input/outputs
- Elevator inputs and outputs with LEDs
- Emergency stop and start up buttons
- 3 floor level sensors (inductive sensor)
- 2 limit sensors (inductive sensör)
- 7 segment floor display
- Arrow shaped LED group showing up/down movement
- Sliding cabin door
- Electromagnetic door lock
- Cabin light
- DC motor
- Dimension: 555mm x 1.180mm x 445 mm

Accessories supplied with set

- IEC power cable
- 20 pcs 4 mm experiment cables
- Sample program software